



## M-LON-HT

PC-HT compounds

### Product Description

M-LON-HT is a high quality PC high temperature recycled compound. This grade is delivered in black color.

Properties	Test conditions	Units	Standard	M-LON
<b>General properties</b>				
MFI	1,2 kg/330 °C	g/10 min	ISO 1133-1	25-55
Charpy Impact Strenght	23 °C	kJ/m <sup>2</sup>	ISO 179-1/1eA	NB
Flammability	-	-	UL-94	HB

#### Notice

This grade is not intended for medical, pharmaceutical, food and drinking water applications. These are typical property values not to be construed as specification limits. Product should be stored in dry conditions at temperatures below 50°C.

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

#### Trademarks

The Trademark referenced within the product name is owned or used by the Maloun s.r.o. company.

#### Bankovní spojení

ČSOB, pobočka Zlín:  
číslo účtu: 379034503/0300 (Kč)  
číslo účtu: 379034773/0300 (Euro)  
SWIFT: CEKOCZPP  
IBAN: CZ05 0300 0000 0003 7903 4773

#### Identifikační údaje

IČO: 49453823  
DIČ: CZ49453823  
Krajský obchodní rejstřík Brno  
oddíl C, vložka 131 03

#### Sídlo firmy, fakturační adresa

**MALOUN, s.r.o. (GmbH)**  
Evropská 661/95  
Vokovice  
160 00 Praha 6  
Tschchechische Republik

#### Provozovna, korespondenční adresa

**MALOUN, s.r.o.**  
Tečovice 369  
763 02 Zlín 4  
Česká republika

#### Kontaktní informace

Tel. ústředna: +420-577-112311  
Fax: +420-577-112321  
E-mail: obchod@maloun.cz  
Doprava: +420-577-112323,  
doprava@maloun.cz  
Internet: www.maloun.cz